

Description		Intelligent Component Series ACTIVAL+™ (Flow measurement and control valve)		
External view		 water		
Model number		FVY51 series		
Type		ISO PN16 type	JIS10K type	JIS20K type
Material: body		Gray, cast iron(EN-GJL-200(EN 1561))	cast iron (FC200)	SCPH2
Pipe size & Cv value	DN15	Cv value : 1~6	Cv value : 1~6	Cv value : 2.5, 6
	DN25	Cv value : 10, 16	Cv value : 10, 16	Cv value : 10, 16
	DN40	Cv value : 25, 40	Cv value : 25, 40	Cv value : 25, 40
	DN50	Cv value : 65	Cv value : 65	Cv value : 65
	DN65	Cv value : 95	Cv value : 95	Cv value : 95
	DN80	Cv value : 125	Cv value : 125	Cv value : 125
	DN100	Cv value : 145	-	-
	DN125	Cv value : 234	-	-
	DN150	Cv value : 350	-	-
Pressure rating	ISO PN16 (1.6MPa)			
Close off rating	DN15-80:1.0MPa, DN125:0.5MPa, DN150:0.4MPa			
Control signal	These three types are available by selecting the desired model number: 1) 4-20mA DC input, RS-485 communication (Modbus™ protocol) 2) 2-10V DC input, RS-485 communication (Modbus™ protocol) 3) 0-10V DC input, RS-485 communication (Modbus™ protocol) 4) SANet (Communication)			

Guide For Building Automation Products

Motor & Valve Edition

SELECTION GUIDE

A complete lineup of products to create the most comfortable indoor environments for office buildings, retail business buildings, and factories.



◆ACTIVAL and ACTIVAL+ are trademarks of Azbil Corporation.

◆Modbus is a trademark and the property of Schneider Electric SE, its subsidiaries and affiliated companies.

Azbil Corporation

Building Systems Company

Yamatake Corporation changed its name to Azbil Corporation on April 1, 2012.

<http://www.azbil.com>

Specifications are subject to change without notice.

Motorized valve ACTIVAL™ series

Compact design — The valve and actuator are integrated as a single unit.

Has a rangeability of 100 :1 and equal percentage characteristics. The SR type is provided with a spring return function.

Description		ACTIVAL		
External view				
Model number		VY51 series		
Type		ISO PN16 / JIS10K type for high differential pressure application		
Material: body		cast iron (FC200), stainless steel (SCS13A) (only for JIS10K)		
Pipe size & Cv value	DN15	Cv value : 1–6	Cv value : 2.5	—
	DN25	Cv value : 10, 16	Cv value : 6.8, 10	—
	DN40	Cv value : 25, 40	Cv value : 16, 25	—
	DN50	Cv value : 65	Cv value : 40	—
	DN65	Cv value : 95	Cv value : 65	—
	DN80	Cv value : 125	Cv value : 95	—
	DN100	—	—	Cv value : 145(ISO PN16), 180(JIS 10K)
	DN125	—	—	Cv value : 234
	DN150	—	—	Cv value : 350
Pressure rating		ISO PN16 / JIS 10K (1.0MPa)		
Close off rating		1.0MPa	0.7MPa	0.5MPa(0.4MPa at DN150)
Control signal		These seven types are available by selecting the desired model number : 1) Floating with 135ohm pot. 2) Nominal 135ohm input 3) 4-20mA DC input 4) 2-10V DC input 5) 0-10V DC input (only for ISO type) 6) 4-20mA (with 4-20mA feedback) 7) SANet (Communication) (Not for high differential pressure application)		
Timing		53–63s		
Power supply		24V AC+/-15% 50/60Hz		
Description		ACTIVAL		
External view				
Model number		VY51 series		
Type		JIS20K type	Spring Return (SR) ISO PN16 / JIS10K type	
Material: body		SCPH2	cast iron (FC200), stainless steel (SCS13A) (only for JIS10K)	
Pipe size & Cv value	DN15	Cv value : 1–6	Cv value : 1–6	
	DN25	Cv value : 10, 16	Cv value : 10,16	
	DN40	Cv value : 25, 40	Cv value : 25, 40	
	DN50	Cv value : 65	Cv value : 65	
	DN65	Cv value : 95	Cv value : 95	
	DN80	Cv value : 125	Cv value : 125	
	Pressure rating	JIS 20K (2.0MPa)	ISO PN16 / JIS 10K (1.0MPa)	
Close off rating		1.0MPa (0.7MPa:80A)	1.0MPa (15A–50A),0.3–1.0MPa(65A),0.1–0.7MPa(80A)	
Control signal		These six types are available by selecting the desired model number : 1) Floating with 135ohm pot. 2) Nominal 135ohm input 3) 4-20mA DC input 4) 2-10V DC input 5) 0-10V DC input (only for SR type) 6) 4-20mA (with 4-20mA feedback) (only for SR type)		
Timing		53–63s	53–63s(using SR : 8 to 60s)	
Power supply		24V AC+/-15% 50/60Hz		

Quick and simple installation! — has a "One-touch lever-locking" mechanism

Compact design! — The 2-way valve has an equal-percentage characteristic, and the 3-way valve has a linear characteristic. The 3-way valve can be used for mixing or diverting applications.

Description		ACTIVAL		
External view				
Model number		VY5302A		
Type		ISO PN16 (1.6MPa)		
Actuator		MY53X0A		
Material: body		Cast bronze		
Pipe size & Cv value	DN15	Cv value : 2.5,4.0		
	DN20	Cv value : 6.3		
	DN25	Cv value : 10		
	DN32	Cv value : 16		
	DN40	Cv value : 25,40		
	DN50	Cv value : 40		
	DN65	—		
	DN80	Cv value : 75		
Pressure rating		Cv value : 110		
Close off rating		PN16 (1.6MPa)		
Control signal		These seven types are available by selecting the desired model number : 1) Floating with 135ohm pot. 2) Nominal 135ohm input 3) 4-20mA DC input 4) 2-10V DC input 5) 0-10V DC input 6) Floating (3-position) 7) SANet (Communication)		
Timing		60s		
Power supply		AC 24V+/-15%		
Description		ACTIVAL		
External view				
Model number		VY5303 (three-way valve)		
Type		JIS10K type		
Material: body		cast iron (FC200)		
Pipe size & Cv value	DN20	Cv value : 4.0, 6.3		
	DN25	Cv value : 10		
	DN32	Cv value : 16		
	DN40	Cv value : 25		
Pressure rating		PN16 (1.6MPa)		
Close off rating		0.5MPa (DN 20,25) 0.3MPa (DN 32,40)		
Control signal		These seven types are available by selecting the desired model number : 1) Floating with 135ohm pot. 2) Nominal 135ohm input 3) 4-20mA DC input 4) 2-10V DC input 5) 0-10V DC input 6) Floating (3-position) 7) SANet (Communication)		
Timing		50/60s (50/60Hz)		
Power supply		24V AC +/-15% 50/60Hz		
Description		ACTIVAL		
External view				
Model number		VY54X0F (three-way valve)		
Type		JIS10K type		
Material: body		cast iron (FC200)		
Pipe size & Cv value	DN50	Cv value:45		
	DN65	Cv value:70		
	DN80	Cv value:100		
Pressure rating		JIS10K (1.0MPa)		
Close off rating		0.3MPa (DN50) 0.2MPa (DN65) 0.15MPa (DN80)		
Control signal		These five types are available by selecting the desired model number : 1) Floating with 135ohm pot. 2) Nominal 135ohm input 3) 4-20mA DC input 4) 2-10V DC input 5) 0-10V DC input 6) Floating (3-position) 7) SANet (Communication)		
Timing		34–42s		
Power supply		100V AC, 200V AC 50/60Hz		
Description		3-way mixing valve + High torque actuator		
External view				
Model number		V5065A		
Type		V5065A		
Valve linkage /yoke set		QMY9400A1001(-DN80) QMY9400B1001(DN100-)		
Actuator		MY9402(-DN80) MY9403(DN100-)		
Valve	DN100	Cv value:188		
	DN125	Cv value:280		
	DN150	Cv value:360		
Pressure Rating		PN10 (1.0MPa)		
Control signal		Floating with 135ohm pot.		
Timing		34–42s		
Power supply		24V AC +/-15% 50/60Hz		